

Decorative iridescent paint with pearl effect

Water dispersion interior paint

INTENDED USE

BALITURA Accento is an iridescent interior paint with pearlescent reflections. The paint is available in 6 colours, factory prepared and tinted, ensuring consistency of quality and colour. The extremely beautiful and elegant pearlescent look is combined with impressive reflections and the iridescent effect of the colours. Combined in one product, these effects give a huge variety of design solutions and make **BALITURA Accento** the ideal finishing touch for any modern home.

The purpose of the paint is to make a fine decorative finish on walls and ceilings of interior rooms. It has a short drying time and excellent coverage. One litre of paint is sufficient for up to 8 m².

BALITURA Accento is water soluble, harmless and does not contain solvents, volatile organic compounds and chemical ingredients hazardous to health and the environment.

PROPERTIES

- ❖ ready to use
- ❖ excellent coverage
- ❖ easy to apply
- ❖ short drying time
- ❖ non-toxic

SURFACE PREPARATION

BALITURA Accento is suitable for work on gypsum plaster and gypsum plasterboard substrates, after mandatory priming. The substrate must be smooth, dry and well cleaned. The joints in plasterboard must be filled and the boards plastered. Old paint or other non-load bearing coatings must be washed or mechanically removed.

To equalise the absorption capacity, improve adhesion, de-dust, and match the colour to that of the paint, the substrate should be primed with the specially developed **BALITURA FONDO**, primer included in the kit, tinted to the colour of the paint.



LAYING AND PROCESSING

BALITURA Accento is ready for use once it has been stirred to achieve a homogeneous colour. The use of paper tape is recommended to protect adjacent walls or existing flooring.

BALITURA Accento is applied in one coat with a brush, dilution of the material with up to 5% water is allowed. The working process must be uninterrupted, from edge to edge, with short movements and without great pressure on the tool.

The drying time of the applied layer is about 6 hours.

CONSUMPTION

- approx. 0,120 – 0,165 l/m²

WORKING TOOLS

- paper tape
- brush

ATMOSPHERIC WORKING CONDITIONS

The product is intended for interior use. The minimum daytime air and substrate temperature should not be lower than +5°C and the maximum temperature should not be higher than +30°C.

DELIVERY PACKAGING

Two plastic packs of 1 l in a carton. Set includes 1 paint and 1 primer.

NOTES

TECHNICAL DATA SHEET

BALITURA ACCENTO

The product characteristics and technical data specified in this process card are determined at standard temperature (20°C) and relative humidity (50%). Under other climatic conditions, the process times for some of the above processes may be shortened or extended.

The product information is based on the manufacturer's practical experience and technical tests in specialized laboratories.

Do not mix with other construction materials.

decorative paint®
Balitura

All warnings and safety recommendations regarding **BALITURA Accento** can be checked in the Product Safety Data Sheet.

STORAGE

24 months in original sealed packaging at temperatures from +5°C to +30°C. Keep away from frost and direct sunlight.

CHARACTERISTICS AND TECHNICAL DATA

Color	By catalogue
Form (aggregate state)	liquid
Drying time	6 hours
Density	1,32 g/cm ³
Adhesion to substrate	3,19 N/mm ²
pH - value	7,8
Content of non-volatile substances	62,62 %
Water permeability coefficient – w	0,23 kg/m ² .h ^{0,5} (class W ₂)

The manufacturer is responsible for the quality of the product, but not for the manner and conditions of its application. The information in this technical data sheet is reliable provided that the product is used under the specified conditions. Any other use of the product, including use in combination with another product or process, is the sole responsibility of the user.