

BALITURA ARAZZO

decorative paint®
Balitura

Decorative plaster with stunning relief and glare

Water dispersion interior plaster

INTENDED USE

BALITURA ARAZZO is an interior water dispersion plaster to which reflective particles can be added. It is available in 10 colours, factory prepared and tinted, guaranteeing consistency of quality and colour. The extremely beautiful and airy look of the plaster is perfectly complemented by a special pearl base, which further enhances the aesthetic effect and gives a huge variety of design solutions, making **BALITURA ARAZZO** an exceptional finishing touch for any modern home.

The purpose of the product is to make a fine decorative coating on walls and ceilings of interior rooms. It has a short drying time and excellent coverage. One litre of the product is sufficient for up to 6 m².

BALITURA ARAZZO is water soluble, it is non-toxic and does not contain solvents, volatile organic compounds and chemical ingredients hazardous to health and the environment.

PROPERTIES

- ❖ ready to use
- ❖ excellent coverage
- ❖ easy to apply
- ❖ short drying time
- ❖ non-toxic

SURFACE PREPARATION

BALITURA ARAZZO is suitable for work on gypsum plaster and gypsum plasterboard substrates, after mandatory priming. The substrate must be smooth, dry and well cleaned. The joints in plasterboard must be filled and the boards plastered. Old paint or other non-load bearing coatings must be washed or mechanically removed.

To even out the absorption capacity, improve adhesion, de-dusting, and uniform the colour with that of the final product, the substrate should be primed with the specially developed **BALITURA FONDO** primer included in the kit, tinted to the colour of the plaster.



LAYING AND PROCESSING

BALITURA ARAZZO is ready for use once it has been stirred to achieve a homogeneous colour. The use of paper tape is recommended to protect adjacent walls or existing flooring.

BALITURA ARAZZO is applied in two coats. The first is a base coat and is applied with a paint roller like paint. Optionally, decorative glitter particles included in the kit can be added to the plaster. Stir with smooth movements, by hand. The second coat is the plaster and is applied after the previous coat has dried/ minimum 4 hours/ by pressing in haphazardly or by "tapping" with a finishing trowel. Allow to stand for 7-8 minutes to dry slightly and smooth with very light pressure of the finishing trowel. Thinning of the materials is not allowed. Work continuously, edge to edge, in short movements and without much pressure on the tool.

The drying time for the second layer is about 6 hours.

CONSUMPTION

- approx. 0,165 – 0,250 l/m²

WORKING TOOLS

- paper tape
- paint roller
- finishing trowel

ATMOSPHERIC WORKING CONDITIONS

The product is intended for interior use. The minimum daytime air and substrate temperature should not be lower than +5°C and the maximum temperature should not be higher than +30°C.

DELIVERY PACKAGING

TECHNICAL DATA SHEET

BALITURA ARAZZO

Three plastic packs of 1 litre and a pack of decorative glitter particles in a cardboard box. Set includes 1 piece of base, 1 piece of plaster, 1 piece of decorative glitter particles and 1 piece of primer.

NOTES

The product characteristics and technical data specified in this process card are determined at standard temperature (20°C) and relative humidity (50%). Under other climatic conditions, the process times for some of the above processes may be shortened or extended.

decorative paint®
Balitura

The product information is based on the manufacturer's practical experience and technical tests in specialized laboratories.

Do not mix with other construction materials.

All warnings and safety recommendations regarding **BALITURA ARAZZO** can be checked in the Product Safety Data Sheet.

STORAGE

24 months in original sealed packaging at temperatures from +5°C to +30°C. Keep away from frost and direct sunlight.

CHARACTERISTICS AND TECHNICAL DATA

Color	By catalogue
Form (aggregate state)	liquid
Drying time	6 hours
Density	1,52 g/cm ³
Adhesion to substrate	3,19 N/mm ²
pH - value	7,8
Content of non-volatile substances	62,62 %
Water permeability coefficient – w	0,23 kg/m ² .h ^{0,5} (class W ₂)

The manufacturer is responsible for the quality of the product, but not for the manner and conditions of its application. The information in this technical data sheet is reliable provided that the product is used under the specified conditions. Any other use of the product, including use in combination with another product or process, is the sole responsibility of the user.