

Decorative satin plaster with impressive relief

Water dispersion interior plaster

INTENDED USE

BALITURA ARAZZO Matto is an interior water dispersion plaster. It is available in 10 colours, factory prepared and tinted, which guarantees consistency of quality and colour. The exceptionally beautiful and airy look of the plaster is perfectly sealed by a special satin finish, which further enhances the aesthetic effect and gives a huge variety of design solutions, making **BALITURA ARAZZO Matto** an exceptional finishing touch for any modern home.

The purpose of the product is to make a fine decorative coating on walls and ceilings of interior rooms. It has a short drying time and excellent coverage. One litre of the product is sufficient for up to 6 m².

BALITURA ARAZZO Matto is water soluble, non-toxic and does not contain solvents, volatile organic compounds and chemical ingredients hazardous to health and the environment.

PROPERTIES

- ❖ ready to use
- ❖ excellent coverage
- ❖ easy to apply
- ❖ short drying time
- ❖ non-toxic

SURFACE PREPARATION

BALITURA ARAZZO Matto is suitable for work on gypsum plaster and gypsum plasterboard substrates after mandatory priming. The substrate must be smooth, dry and well cleaned. Joints in plasterboard must be filled and boards plastered. Old paint or other non-load bearing coatings must be washed or mechanically removed.

To equalise the absorption capacity, improve adhesion, de-dust, and match the colour to that of the finished product, the substrate should be primed with the specially developed **BALITURA FONDO** primer included in the kit, tinted to the colour of the plaster.



LAYING AND PROCESSING

BALITURA ARAZZO Matto is ready for use once it has been stirred to achieve a homogeneous colour. The use of paper tape is recommended to protect adjacent walls or existing flooring.

BALITURA ARAZZO Matto is applied in two coats. The first one is a plaster and is applied after the primer has dried/ minimum 4 hours/ by pressing the material or by "tapping" with a finishing trowel. Allow to stand for 7-8 minutes to dry slightly and smooth with very light pressure of the finishing trowel. The final satin finish is in the colour of the plaster and is applied with a paint roller as a paint 6-8 hours after the previous coat has worn off.

Thinning of the materials is not allowed. Work continuously, edge to edge, in short movements and without much pressure on the tool.

The drying time for the second layer is about 6 hours.

CONSUMPTION

- approx. 0,165 – 0,250 l/m²

WORKING TOOLS

- paper tape
- paint roller
- finishing trowel

ATMOSPHERIC WORKING CONDITIONS

The product is intended for interior use. The minimum daytime air and substrate temperature should not be lower than +5°C and the maximum temperature should not be higher than +30°C.

DELIVERY PACKAGING

TECHNICAL DATA SHEET

BALITURA ARAZZO Matto

Three plastic packs of 1 l in a carton. Set includes 1 decorative coating, 1 plaster and 1 primer.

NOTES

The product characteristics and technical data specified in this process card are determined at standard temperature (20°C) and relative humidity (50%). Under other climatic conditions, the process times for some of the above processes may be shortened or extended.

decorative paint®
Balitura

The product information is based on the manufacturer's practical experience and technical tests in specialized laboratories.

Do not mix with other construction materials.

All warnings and safety recommendations regarding **BALITURA ARAZZO Matto** can be checked in the Product Safety Data Sheet.

STORAGE

24 months in original sealed packaging at temperatures from +5°C to +30°C. Keep away from frost and direct sunlight.

CHARACTERISTICS AND TECHNICAL DATA

Color	By catalogue
Form (aggregate state)	liquid
Drying time	6 hours
Density	1,52 g/cm ³
Adhesion to substrate	3,19 N/mm ²
pH - value	7,8
Content of non-volatile substances	62,62 %
Water permeability coefficient – w	0,23 kg/m ² .h ^{0,5} (class W ₂)

The manufacturer is responsible for the quality of the product, but not for the manner and conditions of its application. The information in this technical data sheet is reliable provided that the product is used under the specified conditions. Any other use of the product, including use in combination with another product or process, is the sole responsibility of the user.