

TECHNICAL DATA SHEET

BALITURA Stucco Veneziano

Decorative plaster with mirror effect

Water dispersion interior plaster

INTENDED USE

BALITURA Stucco Veneziano is an acrylate paste based interior water dispersion plaster. The plaster is available in 10 colours, factory prepared and tinted, which guarantees consistency of quality and colour. The exceptionally beautiful glossy look and smoothness, resembling a mirror effect, give a huge variety of design solutions and make **BALITURA Stucco Veneziano** an ideal solution for finishing walls and ceilings in any modern home.

The plaster is designed to make a fine decorative finish on individual elements as well as overall on walls and ceilings of interior rooms. It has a short drying time and excellent coverage. The package is sufficient for up to 6 m².

BALITURA Stucco Veneziano is water soluble, it is non-toxic and does not contain solvents, volatile organic compounds and chemical ingredients hazardous to health and the environment.

PROPERTIES

- ❖ ready to use
- ❖ excellent coverage
- ❖ excellent smoothness
- ❖ short drying time
- ❖ non-toxic

SURFACE PREPARATION

BALITURA Stucco Veneziano is suitable for work on gypsum plaster and gypsum plasterboard substrates, after mandatory priming. The substrate must be smooth, dry and well cleaned. The joints in plasterboard must be filled and the boards plastered. Old paint or other non-load bearing coatings must be washed or mechanically removed.

To equalize the absorption capacity, improve adhesion and dust removal, the substrate should be primed with the specially developed **BALITURA FONDO** primer included in the kit.

decorative paint®
Balitura



LAYING AND PROCESSING

BALITURA Stucco Veneziano is ready for use once it has been stirred to achieve a homogeneous colour. The use of paper tape is recommended to protect adjacent walls or existing flooring.

BALITURA Stucco Veneziano is applied in three coats using a rounded-angled finishing trowel. The material should not be thinned. Work continuously, edge to edge, in short movements and with pressure on the tool.

It is recommended to wait a minimum of 6 hours between coats during application of **BALITURA Stucco Veneziano**. The third coat is cycled with maximum pressure while still wet to achieve a gloss surface.

The drying time required for the last layer of plaster applied is approximately 6 hours.

CONSUMPTION

- approx. 0,330 l/m² with 3 coats

WORKING TOOLS

- paper tape
- rounded-angled finishing trowel

ATMOSPHERIC WORKING CONDITIONS

The product is intended for interior use. The minimum daytime air and substrate temperature should not be lower than +5°C and the maximum temperature should not be higher than +30°C.

DELIVERY PACKAGING

Three plastic packs of 1 l in a carton. Set includes 2 pieces of plaster and 1 piece of primer.

NOTES

TECHNICAL DATA SHEET

BALITURA Stucco Veneziano

decorative paint®
Balitura

The product characteristics and technical data specified in this process card are determined at standard temperature (20°C) and relative humidity (50%). Under other climatic conditions, the process times for some of the above processes may be shortened or extended.

The product information is based on the manufacturer's practical experience and technical tests in specialized laboratories.

Do not mix with other construction materials.

All warnings and safety recommendations regarding **BALITURA Stucco Veneziano** can be checked in the Product Safety Data Sheet.

STORAGE

24 months in original sealed packaging at temperatures from +5°C to +30°C. Keep away from frost and direct sunlight.

CHARACTERISTICS AND TECHNICAL DATA

Color	By catalogue
Form (aggregate state)	liquid
Drying time	6 hours
Density	1,52 g/cm ³
Adhesion to substrate	3,19 N/mm ²
pH - value	7,8
Content of non-volatile substances	62,62 %
Water permeability coefficient – w	0,23 kg/m ² .h ^{0,5} (class W ₂)

The manufacturer is responsible for the quality of the product, but not for the manner and conditions of its application. The information in this technical data sheet is reliable provided that the product is used under the specified conditions. Any other use of the product, including use in combination with another product or process, is the sole responsibility of the user.