

BALITURA DI PERLA

decorative paint®
Balitura

Decorative paint with pearlescent effect

Water dispersion interior paint

INTENDED USE

BALITURA DI PERLA is an interior water dispersion paint with a fine sand structure incorporated in it. The paint is available in 10 colours, factory prepared and tinted, guaranteeing consistency of quality and colour. The extremely elegant look and rich pearl colour fairy give a huge variety of design solutions and make **BALITURA DI PERLA** the ideal finishing touch for any modern home.

The purpose of the product is to make a fine decorative coating on walls and ceilings of interior rooms. It has a short drying time and excellent coverage. One liter of paint is enough for up to 8 m².

BALITURA DI PERLA is waterborne, harmless and does not contain solvents, volatile organic compounds and chemical ingredients hazardous to health and the environment.

PROPERTIES

- ❖ ready to use
- ❖ excellent coverage
- ❖ easy to apply
- ❖ short drying time
- ❖ non-toxic

SURFACE PREPARATION

BALITURA DI PERLA is suitable for work on gypsum plaster and gypsum plasterboard substrates, after mandatory priming. The substrate must be smooth, dry and well cleaned. The joints in plasterboard must be filled and the boards plastered. Old paint or other non-load bearing coatings must be washed or mechanically removed.

To equalise the absorption capacity, improve adhesion, dustproofing, and uniform the colour with that of the plaster, the substrate should be primed with the specially developed **BALITURA FONDO** primer included in the kit, tinted to the colour of the plaster.



LAYING AND PROCESSING

BALITURA DI PERLA is ready for use once it has been stirred to achieve a homogeneous colour. The use of paper tape is recommended to protect adjacent walls or existing flooring.

BALITURA DI PERLA is applied in a single coat using a brush, allowing up to 10% dilution with water. Work process has to be continuous, edge to edge, in short strokes.

The required drying time is about 6 hours after the coat is completed.

CONSUMPTION

- approx. 0,125 – 0,145 l/m²

WORKING TOOLS

- paper tape
- brush

ATMOSPHERIC WORKING CONDITIONS

The product is intended for interior use. The minimum daytime air and substrate temperature should not be lower than +5°C and the maximum temperature should not be higher than +30°C.

DELIVERY PACKAGING

TECHNICAL DATA SHEET

BALITURA DI PERLA

Two plastic packs of 1 l in a carton. Set includes 1 paint and 1 primer.

NOTES

The product characteristics and technical data specified in this process card are determined at standard temperature (20°C) and relative humidity (50%). Under other climatic conditions, the process times for some of the above processes may be shortened or extended.

decorative paint®
Balitura

The product information is based on the manufacturer's practical experience and technical tests in specialized laboratories.

Do not mix with other construction materials.

All warnings and safety recommendations regarding **BALITURA DI PERLA** can be checked in the Product Safety Data Sheet.

STORAGE

24 months in original sealed packaging at temperatures from +5°C to +30°C. Keep away from frost and direct sunlight.

CHARACTERISTICS AND TECHNICAL DATA

Color	By catalogue
Form (aggregate state)	liquid
Drying time	6 hours
Density	1,52 g/cm ³
Adhesion to substrate	3,19 N/mm ²
pH - value	7,8
Content of non-volatile substances	62,62 %
Water permeability coefficient – w	0,23 kg/m ² .h ^{0,5} (class W ₂)

The manufacturer is responsible for the quality of the product, but not for the manner and conditions of its application. The information in this technical data sheet is reliable provided that the product is used under the specified conditions. Any other use of the product, including use in combination with another product or process, is the sole responsibility of the user.