

BALITURA VIA VELLUTO

decorative paint®
Balitura

Velvet pearlescent coating

Water dispersion decorative coating for interior application

INTENDED USE

BALITURA VIA VELLUTO is an interior water dispersion coating. The product is available in 8 colours, factory prepared and tinted, which guarantees consistency of quality and colour. The exceptionally beautiful and elegant look, combining velvety softness and pearlescent shades, gives a huge variety of design solutions and makes **BALITURA VIA VELLUTO** the ideal finishing touch that every cosy home needs.

The product is intended for making a fine decorative coating on walls and ceilings of interior rooms. It has a short drying time and excellent coverage - one litre is enough for up to 8 m².

BALITURA VIA VELLUTO is a waterborne, harmless coating that does not contain solvents, volatile organic compounds and chemical ingredients hazardous to health and the environment.

PROPERTIES

- ❖ ready to use
- ❖ excellent coverage
- ❖ easy to apply
- ❖ short drying time
- ❖ non-toxic

SURFACE PREPARATION

Decorative interior coating **BALITURA VIA VELLUTO** is suitable for work on gypsum plaster and gypsum plasterboard substrates, after mandatory priming. The substrate must be smooth, dry and well cleaned. The joints in plasterboard must be filled and the boards plastered. Old paint or other non-load bearing coatings must be washed or mechanically removed.



To equalise the absorption capacity, improve adhesion, de-dusting, and uniform the colour with that of the coating, the substrate should be primed with the specially developed **BALITURA FONDO** primer included in the kit.

LAYING AND PROCESSING

BALITURA VIA VELLUTO velvet coating is ready for use after being mixed until a homogeneous colour is achieved. The use of paper tape is recommended to protect adjacent walls or existing flooring.

BALITURA VIA VELLUTO is applied in two coats using a brush. It is worked continuously, edge to edge, with short varied movements and without much pressure on the tool. After the first coat has dried, a second coat is applied, here it is allowed to dilute the material with up to 10% water.

The drying time for one coat is about 6 hours.

CONSUMPTION

- approx. 0,125 – 0,165 l/m²

WORKING TOOLS

- paper tape
- brush

ATMOSPHERIC WORKING CONDITIONS

The product is intended for interior use. The minimum daytime air and substrate temperature should not be lower than +5°C and the maximum temperature should not be higher than +30°C.

DELIVERY PACKAGING

Two plastic packs of 1 l in a carton. Set includes 1 paint and 1 primer.

TECHNICAL DATA SHEET

BALITURA VIA VELLUTO

NOTES

The product characteristics and technical data specified in this process card are determined at standard temperature (20°C) and relative humidity (50%). Under other climatic conditions, the process times for some of the above processes may be shortened or extended.

The product information is based on the manufacturer's practical experience and technical tests in specialized laboratories.

CHARACTERISTICS AND TECHNICAL DATA

Color	By catalogue
Form (aggregate state)	liquid
Drying time	6 hours
Density	1,52 g/cm ³
Adhesion to substrate	3,19 N/mm ²
pH - value	7,8
Content of non-volatile substances	62,62 %
Water permeability coefficient – w	0,23 kg/m ² .h ^{0,5} (class W ₂)

The manufacturer is responsible for the quality of the product, but not for the manner and conditions of its application. The information in this technical data sheet is reliable provided that the product is used under the specified conditions. Any other use of the product, including use in combination with another product or process, is the sole responsibility of the user.

decorative paint ®
Balitura

Do not mix with other construction materials.

All warnings and safety recommendations regarding **BALITURA VIA VELLUTO** can be checked in the Product Safety Data Sheet.

STORAGE

24 months in original sealed packaging at temperatures from +5°C to +30°C. Keep away from frost and direct sunlight.